

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
23 December 2004 (23.12.2004)

PCT

(10) International Publication Number
WO 2004/110675 A1

(51) International Patent Classification⁷: **B22D 2/00**,
11/18, 37/00, G01N 27/74, 33/20, C21C 5/46

(74) Agent: **AWAPATENT AB**; Box 11394, S-404 28 Göteborg (SE).

(21) International Application Number:
PCT/EP2004/004314

(22) International Filing Date: 23 April 2004 (23.04.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
03013294.8 13 June 2003 (13.06.2003) EP

(71) Applicant (for all designated States except US): **MPC METAL PROCESS CONTROL AG** [SE/SE]; P.O. Box 287, S-611 26 Nyköping (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **JALK, Mats** [SE/SE]; V. Kvarngatan 1, S-611 31 Nyköping (SE). **OHLSSON, Willy** [SE/SE]; V. Kvarngatan 19, S-611 31 Nyköping (SE). **KELVESJÖ, Håkan** [SE/SE]; Box 287, S-611 26 Nyköping (SE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: A METHOD AND A DEVICE FOR DETECTING SLAG



(57) Abstract: The invention relates to a method and a device of detecting the presence of slag in a shroud (4) through which molten metal passes from a ladle (2) to a tundish (6). An induced voltage generated at a receiving coil (24) is compared with a defined voltage range. If the induced voltage has a value outside the defined voltage range it is indicative of the presence of slag. The voltage range is defined in dependence of the flow of molten metal passing through the shroud. The invention also relates to a casting plant.

WO 2004/110675 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.